

TECHNICAL DATA SHEET

SELLEYS READY MIXED WALLPAPER ADHESIVE

PHYSICAL DATA

Appearance	:	Beige
Solid Content	:	42 - 46%
Viscosity at 30 °C	:	22000 - 30000 cps

CHARACTERISTICS

- Selleys Ready Mixed Wallpaper Adhesive is a ready to use wallpaper and lining paper adhesive and has been designed to roller or brush directly from the tub for your convenience.
- It is suitable for hanging all types of lining papers and wallpapers.
- No mixing or dilution is required.
- The super smooth, easy spread adhesive has strong grab and easy slide for perfect wallpaper hanging.

DIRECTIONS

- Surface must be flat and clean. Wipe off all moisture, oil and other foreign matters on wall surface.
- Paint layer and former wallpaper must be scrap off for maximum wallpaper adhesion.
- Use a brush or roller to apply Selleys Wallpaper Adhesive on the back of wallpaper. Start from the middle of wallpaper and towards the edge of wallpaper.

TECHNICAL DATA SHEET

SELLEYS READY MIXED WALLPAPER ADHESIVE

- Please stick the wallpaper from top of the wall to down position.
- Smoothing the wallpaper from the center outward using plastic scrapper.
- You have about 5 to 10 minutes to perfect placement of wallpaper. Carefully push any bubbles out toward the borders.
- Wash off excess adhesive with a damp natural sponge.

SAFETY DIRECTION WARNING. CAUSES EYE IRRITATION

- Keep out of reach of children. Read label before use. Avoid skin and eye contact and breath vapours. Wash all exposed skin thoroughly after handling. Additional information is listed in the Safety Data Sheet.

FIRST AID

- If medical advise is needed, have product container at hand.
- If in eyes, rinse with water at least 15 minutes and seek medical advice.

STORAGE

- Store in cool, dry conditions between +5 and 25°C.

Every endeavor has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. User are advised to confirm suitability of this product by their own tests.